

## COMMAND & CONTROL CONTAINER SYSTEMS

# Command Post Shelter 1:2



➤ For a Command & Control crew, it is essential that the workplace is safe, comfortable and efficient and can easily be transported. RUAG provides high-tech expandable command and control posts that fold into ISO standard 20-foot containers for transport. The containers are CSC-approved and fulfill the military standards.

### ➤ FEATURES

- Up to 17 m<sup>2</sup> of workspace
- Protection against NBC threats
- EMC and NEMP protection
- RF shielding (TEMPEST)
- Ballistic protection
- Automatic unfolding with electric drives

### ➤ KEY ADVANTAGES

- Easy to transport and deployable in any terrain worldwide
- Quick set-up without additional equipment
- Ensures safety of personnel and equipment in extreme environmental conditions
- Provides comfortable and efficient workspace in a climate-controlled environment
- Autonomous operation thanks to integrated supply systems
- Expandable and highly adaptable to various tasks
- High quality thanks to Swiss quality standards
- Worldwide service and assistance provided by RUAG specialized technicians

## COMMAND & CONTROL CONTAINER SYSTEMS

### COMMAND POST SHELTER 1:2

01:21

#### ➤ DIMENSIONS & RATING

Container type according to ISO 668		1C	1CC
Length	external (transport mode) / internal (operation mode)	6,058 mm / 4,200 – 4,700 mm	6,058 mm / 4,200 – 4,700 mm
Width	external (transport mode) / internal (operation mode)	2,438 mm / 3,950 mm	2,438 mm / 3,950 mm
Height	external (transport mode) / internal (operation mode)	2,438 mm / 2,000 mm – 2,150 mm	2,591 mm / 2,150 mm – 2,300 mm
Floor space in operation		17 m <sup>2</sup>	17 m <sup>2</sup>
Max gross weight		14,500 kg	14,500 kg
Payload		7,100 kg	6,700 kg
Container weight (basic version)		7,400 kg	7,800 kg

#### ➤ OPERATING CONDITIONS & APPROVALS

Transportability	Ship	CSC approval (213,360 kg stacking weight)
	Road	Truck & trailer transport on road & unpaved, heavy terrain [Mil Std 810]
	Railway	UIC 81
	Air transport	Mil Std 810 (interior load: up: 3.0 g; down: 4.5 g; side: 1.5 g; axial: 1.5 g)
Environmental condition	Operation	A1-A3, B1-B3, C0-C1 (AECTP 200 / STANAG 2895)
	Storage	A1-A3, B1-B3, C0-C1 (AECTP 200 / STANAG 2895)
	Solar radiation	Up to 1120 W/m <sup>2</sup> (Diurnal cycle acc. AECTP 200)
Topographic operating altitude	Up to 2,500 m above sea level	
Electrical safety	EMI / EMC	Mil Std 461, AECTP 250, VG95370 – VG 95377, 2014/30/EU
	LEMP / NEMP / HEMP	Mil Std 155-125 (optional)
	RF shielding	> 60 dB (H & E-Field) test-method according to IEEE299
	TEMPEST	Optional
CBRN protection	Optional, prepared interfaces for operator cabin	
Ballistic protection	Up to KE Level 3 according to Stanag 4569 / AEP 55 Vol. 1 (optional)	

#### ➤ AIR CONDITIONING SYSTEM

Direct evaporating air conditioner (compact or split unit)	
Cooling capacity	Standard 8 kW (up to 14 kW)
Heating capacity	4 kW electrical heating
Fossil auxiliary heater	Optional
Breathing air supply	According to Mil Std 1472

#### ➤ BASIC ELECTRICAL EQUIPMENT

External supply voltage	230 / 400 V-AC 50 Hz
Fuse box	Operator & technical compartment
Lighting / Illumination	300 Lux / m <sup>2</sup> ceiling integrated
Power sockets	230 V-AC integrated into ducts
Server racks & IT cabling	According to TEMPEST requirements

#### ➤ INTERIOR FITTINGS

	Standard	Option
Thermal insulation & smooth inner wall	×	
Signal line interface box to operator compartment	×	
C-Rails on side walls, ceiling & floor	×	
Air distribution with textile hoses	×	
Wall / ceiling-integrated air distribution system		×
Door and walls with windows		×
Material cabinet below HVAC system outside		×

#### ➤ FUNCTIONAL EQUIPMENT

	Standard	Option
Workplace with office chair	×	
Power generator		×
Isolation transformer		×
Uninterruptible Power Supply (UPS)		×
Server racks with shock absorber		×
Entrance tent		×
Customized electrical installation inside		×